

| STW Series | | | | | | | | | |
|---|--|-------------|------------------------|----------------------|-----------|---------------|-------------------|------------------|-------|
| DI Body, S/S Disc, Butterfly Valve, Wafer, EPDM seats with Direct Mount Actuator | | | | | | | | | |
| Pneumatic Actuators | | | | | | | | | |
| Spring Return | | | | Double Acting | | | | | |
| | 80 PSIG | | 60 PSIG | | 80 PSIG | | 60 PSIG | | |
| | *STW-SO8S** | *STW-SE8S** | STW-SO6S** | STW-SE6S** | *STW-SO8D | *STW-SE8D | *STW-SO6D | *STW-SE6D | |
| H 2" | \$ 361 | \$ 497 | \$ 476 | \$ 524 | \$ 340 | \$ 373 | \$ 340 | \$ 373 | |
| I 2½" | \$ 402 | \$ 538 | \$ 517 | \$ 565 | \$ 381 | \$ 414 | \$ 381 | \$ 414 | |
| J 3" | \$ 421 | \$ 557 | \$ 536 | \$ 584 | \$ 400 | \$ 433 | \$ 400 | \$ 433 | |
| K 4" | \$ 452 | \$ 588 | \$ 567 | \$ 615 | \$ 431 | \$ 465 | \$ 431 | \$ 465 | |
| L 5" | \$ 550 | \$ 863 | \$ 816 | \$ 863 | \$ 487 | \$ 595 | \$ 487 | \$ 618 | |
| M 6" | \$ 690 | \$ 930 | \$ 883 | \$ 930 | \$ 651 | \$ 685 | \$ 651 | \$ 837 | |
| N 8" | \$ 1,032 | \$ 1,332 | \$ 1,405 | \$ 1,332 | \$ 800 | \$ 986 | \$ 800 | \$ 986 | |
| O 10" | \$ 1,700 | \$ 2,402 | \$ 1,987 | \$ 2,928 | \$ 1,261 | \$ 1,461 | \$ 1,397 | \$ 1,461 | |
| P 12" | \$ 1,892 | \$ 3,120 | \$ 2,658 | \$ 3,120 | \$ 1,453 | \$ 1,653 | \$ 1,589 | \$ 2,205 | |
| * Size Code ** Fail Position: C=Closed, O=Open | | | | | | | | | |
| Material Codes: "-":B=Buna or E=EPDM | | | | | | | | | |
| Electric Actuators | | | | | | | | | |
| | NEMA 4 | | Explosion Proof | | | Manual | | | |
| | *STW-SK4A | *STW-SO4** | *STW-SN7A | | | *STW-SM | | | |
| H 2" | 835 | 1215 | 1831 | | | \$ 79 | | | |
| I 2½" | 876 | 1256 | 1872 | | | \$ 96 | | | |
| J 3" | 895 | 1275 | 1891 | | | \$ 115 | | | |
| K 4" | 926 | 1306 | 1922 | | | \$ 146 | | | |
| L 5" | 982 | 1361 | 1977 | | | \$ 202 | | | |
| M 6" | 1049 | 1824 | 2045 | | | \$ 257 | | | |
| N 8" | 1598 | 1973 | 4220 | | | \$ 406 | | | |
| O 10" | 2693 | #N/A | 4515 | | | \$ 718 | | | |
| P 12" | 2885 | #N/A | 4707 | | | \$ 910 | | | |
| * Size Code Voltage Code: A = 120VAC, ** Use: B(24VDC) or F(12VDC) | | | | | | | | | |
| Material Codes: 1st "-":B=Buna or E=EPDM, 2nd "-": D=Ductile Iron Disc, B=Bronze Disc, S=316SS Disc | | | | | | | | | |
| Accessory items | | | | | | | | | |
| Solenoid Valves | | | | | | | | | |
| Code | | | | | | | | | |
| E1* | 3-Way Nema 4/4X, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 86 |
| E2* | 3-Way Nema 4/4X/7, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 122 |
| E3* | 3-Way Nema 4/4X Din Cord Grip, NAMUR Mount | | | | | | | \$ | 68 |
| E4* | 3-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 77 |
| E5* | 3-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 6' Cord Set | | | | | | | \$ | 94 |
| E6* | 3-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 15' Cord Set | | | | | | | \$ | 102 |
| C1* | 3/4-Way Nema 4/4X, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 122 |
| C2* | 3/4-Way Nema 4/4X/7, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 158 |
| C3* | 3/4-Way Nema 4/4X Din Cord Grip, NAMUR Mount | | | | | | | \$ | 110 |
| C4* | 3/4-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 110 |
| C5* | 3/4-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 6' Cord Set | | | | | | | \$ | 127 |
| C6* | 3/4-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 15' Cord Set | | | | | | | \$ | 135 |
| * Voltage Codes A=120VAC, B = 24VDC, C=220VAC, E=24VAC, F=12VDC, Others Available) | | | | | | | | | |
| Limit Switches | | | | | | | | | |
| YF | Weatherproof 2 SPDT, Mechanical | | | | | | | \$ | 83 |
| YO | Class I, Div II, Proximity Sensor, Lexan Cover | | | | | | | \$ | 516 |
| YH | Class I, Div I, Proximity Sensor, Alum. Cover | | | | | | | \$ | 553 |
| YE | Class I, Div I, Mechanical Switch, Alum. Cover | | | | | | | \$ | 369 |
| UA | Weatherproof Efector IN0117 AC/DC Non-Contact, 2 NO Contacts | | | | | | | \$ | 220 |
| UB | Weatherproof Efector IN5327 DC Non-Contact, 2 NO Contacts | | | | | | | \$ | 204 |
| Manual Valve with Limit Switch | | | | | | | | | |
| Call Factory for Pricing | | | | | | | | | |
| Pneumatic Actuator Positioners | | | | | | | | | |
| P5 | 3-15PSIG input PMV Positioner (w/o gauges) | | | | | | | \$ | 696 |
| E5 | 4-20mADC Input positioners (w/o gauges) | | | | | | | \$ | 1,240 |
| Electric Actuators | | | | | | | | | |
| VEP | V series Electronic Positioner | | | | | | | \$ | 695 |
| | | | | | | | Effective: | 11/1/2008 | |

| STL Series | | | | | | | | | |
|---|--|-------------|-----------------|-------------|---------------|-----------|-------------------|------------------|-------|
| DI Body, S/S Disc, Butterfly Valve, Lug, EPDM seats with Direct Mount Actuator | | | | | | | | | |
| Pneumatic Actuators | | | | | | | | | |
| | Spring Return | | | | Double Acting | | | | |
| | 80 PSIG | | 60 PSIG | | 80 PSIG | | 60 PSIG | | |
| | *STL-SO8S** | *STL-SE8S** | *STL-SO6S** | *STL-SE6S** | *STL-SO8D | *STL-SE8D | *STL-SO6D | *STL-SE6D | |
| H 2" | \$ 366 | \$ 502 | \$ 481 | \$ 529 | \$ 345 | \$ 378 | \$ 345 | \$ 378 | |
| I 2½" | \$ 404 | \$ 540 | \$ 519 | \$ 567 | \$ 383 | \$ 417 | \$ 383 | \$ 417 | |
| J 3" | \$ 430 | \$ 567 | \$ 546 | \$ 594 | \$ 410 | \$ 443 | \$ 410 | \$ 443 | |
| K 4" | \$ 471 | \$ 607 | \$ 586 | \$ 634 | \$ 451 | \$ 484 | \$ 451 | \$ 484 | |
| L 5" | \$ 571 | \$ 884 | \$ 838 | \$ 884 | \$ 508 | \$ 616 | \$ 508 | \$ 639 | |
| M 6" | \$ 714 | \$ 954 | \$ 907 | \$ 954 | \$ 675 | \$ 709 | \$ 675 | \$ 861 | |
| N 8" | \$ 1,075 | \$ 1,375 | \$ 1,448 | \$ 1,375 | \$ 843 | \$ 1,029 | \$ 843 | \$ 1,029 | |
| O 10" | \$ 1,753 | \$ 2,455 | \$ 2,040 | \$ 2,981 | \$ 1,314 | \$ 1,513 | \$ 1,449 | \$ 1,513 | |
| P 12" | \$ 1,995 | \$ 3,223 | \$ 2,762 | \$ 3,223 | \$ 1,557 | \$ 1,756 | \$ 1,692 | \$ 2,308 | |
| Q 14" | #N/A | \$ 4,100 | #N/A | \$ 4,100 | #N/A | \$ 2,633 | #N/A | \$ 2,633 | |
| R 16" | #N/A | \$ 4,595 | #N/A | \$ 4,595 | #N/A | \$ 3,679 | #N/A | \$ 3,679 | |
| S 18" | #N/A | \$ 5,572 | #N/A | \$ 6,678 | #N/A | \$ 4,656 | #N/A | \$ 4,977 | |
| T 20" | #N/A | \$ 8,202 | #N/A | \$ 8,202 | #N/A | \$ 6,180 | #N/A | \$ 6,501 | |
| U 24" | #N/A | \$ 11,766 | #N/A | \$ 15,353 | #N/A | \$ 9,273 | #N/A | \$ 9,273 | |
| * Size Code ** Fail Position: C=Closed, O=Open | | | | | | | | | |
| Material Codes: *-:B=Buna or E=EPDM | | | | | | | | | |
| Electric Actuators | | | | | | | | | |
| | NEMA 4 | | Explosion Proof | | Manual | | | | |
| | *STL-SK4A | *STL-SO4** | *STL-SE7A | | *STL-SM | | | | |
| H 2" | 840 | 1220 | 1836 | | \$ 84 | | | | |
| I 2½" | 878 | 1258 | 1874 | | \$ 98 | | | | |
| J 3" | 905 | 1284 | 1901 | | \$ 125 | | | | |
| K 4" | 946 | 1325 | 1941 | | \$ 166 | | | | |
| L 5" | 1003 | 1383 | 1999 | | \$ 223 | | | | |
| M 6" | 1073 | 1848 | 2069 | | \$ 281 | | | | |
| N 8" | 1641 | 2016 | 4263 | | \$ 449 | | | | |
| O 10" | 2746 | #N/A | 4568 | | \$ 771 | | | | |
| P 12" | 2988 | #N/A | 4810 | | \$ 1,014 | | | | |
| Q 14" | 4895 | #N/A | 5687 | | \$ 1,766 | | | | |
| R 16" | 5389 | #N/A | 6181 | | \$ 2,260 | | | | |
| S 18" | 6366 | #N/A | 7618 | | \$ 3,237 | | | | |
| T 20" | 7890 | #N/A | 9142 | | \$ 4,761 | | | | |
| U 24" | 11101 | #N/A | 11101 | | \$ 6,720 | | | | |
| * Size Code Voltage Code: A = 120VAC, ** Use: B(24VDC) or F(12VDC) | | | | | | | | | |
| Material Codes: 1st "-":B=Buna or E=EPDM, 2nd "-": D=Ductile Iron Disc, B=Bronze Disc, S=316SS Disc | | | | | | | | | |
| Accessory items | | | | | | | | | |
| Solenoid Valves | | | | | | | | | |
| Code | | | | | | | | | |
| E1* | 3-Way Nema 4/4X, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 86 |
| E2* | 3-Way Nema 4/4X/7, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 122 |
| E3* | 3-Way Nema 4/4X Din Cord Grip, NAMUR Mount | | | | | | | \$ | 68 |
| E4* | 3-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 77 |
| E5* | 3-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 6' Cord Set | | | | | | | \$ | 94 |
| E6* | 3-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 15' Cord Set | | | | | | | \$ | 102 |
| C1* | 3/4-Way Nema 4/4X, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 122 |
| C2* | 3/4-Way Nema 4/4X/7, potted 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 158 |
| C3* | 3/4-Way Nema 4/4X Din Cord Grip, NAMUR Mount | | | | | | | \$ | 110 |
| C4* | 3/4-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount | | | | | | | \$ | 110 |
| C5* | 3/4-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 6' Cord Set | | | | | | | \$ | 127 |
| C6* | 3/4-Way Nema 4/4X Din, 1/2" Conduit, NAMUR Mount, 15' Cord Set | | | | | | | \$ | 135 |
| * Voltage Codes A=120VAC, B = 24VDC, C=220VAC, E=24VAC, F=12VDC, Others Available) | | | | | | | | | |
| Limit Switches | | | | | | | | | |
| YF | Weatherproof 2 SPDT, Mechanical | | | | | | | \$ | 83 |
| YO | Class I, Div II, Proximity Sensor, Lexan Cover | | | | | | | \$ | 516 |
| YH | Class I, Div I, Proximity Sensor, Alum. Cover | | | | | | | \$ | 553 |
| YE | Class I, Div I, Mechanical Switch, Alum. Cover | | | | | | | \$ | 369 |
| UA | Weatherproof Efector IN0117 AC/DC Non-Contact, 2 NO Contacts | | | | | | | \$ | 220 |
| UB | Weatherproof Efector IN5327 DC Non-Contact, 2 NO Contacts | | | | | | | \$ | 204 |
| Manual Valve with Limit Switch | | | | | | | | | |
| Call Factory for Pricing | | | | | | | | | |
| Pneumatic Actuator Positioners | | | | | | | | | |
| P5 | 3-15PSIG input PMV Positioner (w/o gauges) | | | | | | | \$ | 696 |
| E5 | 4-20mADC Input positioners (w/o gauges) | | | | | | | \$ | 1,240 |
| Electric Actuators | | | | | | | | | |
| VEP | V series Electronic Positioner | | | | | | | \$ | 695 |
| | | | | | | | Effective: | 11/1/2008 | |